

TRUCKS:SEMI-STOCK&COMPACT

1. Compacts, ½ tons to 1 tons allowed in appropriate classes. No dually's, 4 x 4's allowed with front drive shaft removed.
2. Any welding from the center of front wheels forward is permitted.
3. Driver's door may be reinforced with steel not to extend more than 1" from original body or 4" beyond front to back of door seams. Under floor on driver's side only, you may run channel or angle from frame to rocker and from back of driver's seat to firewall.
4. May install dash pipe no larger than 3" diameter pipe with 5"x5"x¼" pads on each and between front door posts. A kicker may be added from dash pipe to passenger rocker, no larger than 3" diameter with a 5"x5"x¼" pad on the end. A diagonal pipe may be added behind the seat.
5. Cab and box may be bolted down to the frame no more than 8 additional ¾" bolts between cab and box. Washers cannot exceed 6" diameter.
6. Box may be welded to cab with 4-4"x4"x¼" pads on the sides and/or 4-¾" bolts with 4"x4" washers can be used , also a 2"x2" angle iron on top front of box to cab.
7. Tailgates must be welded on and in stock position - **IF TAILGATE FALLS OFF, YOU ARE DISQUALIFIED.**
8. All doors must be tied shut with single loop chain or 6-2"x4" pads per door.
9. One strap per side may be welded over taillight hole, Max of 4" wide ¼" thick and may not exceed 3" beyond each side of the light hole.
10. Radium barrels must be inside frame rails (top and bottom), may be welded or bolted. The barrels can be 3" thick outside to outside and must be vented down.
11. Hoods: All hoods must be able to be opened for inspection; they must have a 12"-14" hole over the carburetor. It would be a good idea to bolt straps to hood or together. 4-¾" rods may be used to hold hood down. Rods may be welded or bolted to the frame.
12. If floor is not there, you may weld in a floor not to exceed 1/8" thickness and may not be welded to the frame. Judges will have a drill and if it is a question it will be checked.
13. Gas tanks: stock tanks must be removed. Trucks must have tank in the box and in front of the rear axle. Max 6 gallon tank and must be securely fastened. (No plastic tanks) No ratchet straps, bungee cords or zip ties allowed.
14. Engine in vehicle does not have to be of the same manufacturer as the body. Motor mounts may be welded. Two additional straps may be used but must be behind the water pump pulley but in front of the carburetor no bigger than ¼"x2"x24" or 2 chains min 5/16" single loop chain 24" long.
15. Look at the general rules as they may apply to every pit person and every driver.
16. Any automotive bumper is allowed.
17. Rear bumpers that are removed, frame rails need to be capped using 4" channel or angle not to extend further than the frame rail width.
18. Suspension welding allowed- **NO LIFT KITS.**