

FULL-SIZE CARS: 1980 & NEWER

1. All cars must be stock-No welding except where noted.
2. Doors can be chained or welded shut. 4 chains or 4 pads per door. Chains to be minimum 5/16" single loop.
3. Hoods can be secured in up to 6 places using either or combination of maximum 3/4" diameter rods or 5/16" single loop chains. Rods or chains can go through /around frame. If using rods, washers to be a maximum of 4"x4".
4. Trunks can be secured in up to 4 places using either or combination of maximum 3/4" diameter rods, or 5/16" single loop chains. Rods or chains can go through/around frame. If using rods, washers to be a maximum of 4"x4".
5. Driver's door may be welded shut. A driver's side door bar is strongly recommended, not to exceed 1 1/2" out from body and no more than 4" past door seams.
6. Stiffening of suspension allowed.
7. Radiators must be in stock position. You may choose to have no cooling system at all. Radii barrels allowed, must be at least 1" inside frame rails 3" maximum outside dimension. Bolted or welded to core support only. May add 2 flat straps to sore support only to hold barrel.
8. Bumpers may be welded or chained on. You may move bumpers back to frame and weld. You can weld factory bumper brackets, no adding of iron to do this.
9. Absolutely NO seam welding on any part of the body or frame will be allowed.
10. For driver's safety only, a brace may be installed behind the driver's seat. It must run diagonally only from window post to rocker, you may add kicker or an X. It must be no larger than 4" pipe or tubing, thick walled material, and plates on each end no bigger than 6" x 6".
11. Dash bar is also permitted. It must be no larger than 4" pipe or tubing, thick walled material, and plates on each end no bigger than 6" x 6".
12. If factory floor is gone (rusted), you may weld in floor not to exceed 1/8" thickness but cannot be welded to sub frame. Judges will have a drill and if it is questionable, it will be checked.
13. Floors may be bolted to sub frame in up to 4 places, using a maximum of 3/4" diameter bolts and 5"x5" plates.
14. Airbags **must** be de-activated before race.
15. Cars must follow all the general preparation rules.