

2021 Chisago County Fair

Antique Class

For questions on this class text your question to 612-290-0092 and we will get back to you with the answer.

1. 1964 and older, No Imperials or frame swaps, Please list make and model on entry form.
2. No whiners! No sand baggers! (This is about putting on a show for the crowd).
3. No tucking quarter panels or trunks. No folding the roof down on wagons.
4. Rust holes in floors may be patched. Up to 1/8" material.
5. Factory body bolts may be replaced. 4-extra body bolts allowed inside the car. 4"x4"x1/4" plates. Cross members must be in stock location. No hump plates.
6. Front bumper: May be replaced with shock type bumper or 1/4" wall square tube or round tube. Ends to remain open. Bumper skin must be welded or bolted.
7. Frame from spindles forward only: may be plated on any 2 sides with flat stock only. A-frames may be welded. No welding on the frame behind the spindles. No stuffing the frame, Hood, trunk lid, or body panels.
8. Lower engine cradles allowed. No mid plates, no dp, no full cradles, no welded motor mounts behind the carb.
9. Angle iron is allowed on top of core support. Front clip can be tied to the frame in 4-places in front of the spindles.
10. Hood must be open for inspection. Can secure hood in 8-places, only 2 threaded rod through the frame at the core support. (up to 1" rod)
11. 4-point floating cage or x braces and dash bar. Cage cannot extend 12" behind the door post. Cage can have 2 vertical kickers to the floor only. (not to the frame)
12. Radi barrel or water tanks are allowed. Water barrel no larger than 2'x2'x2' and must be vented back and down through the floor. Radi barrel must be attached to the core support only. No braces going into the trunk area.
13. Drivers Door reinforcement may not extend more than 2" out from the body and more than 6" past the door seams.
14. Body: doors may be patch welded shut. Up to 5" x 5" patches 4 per door. 2-door models, 6 patches on passenger door. No seam weld.
15. Trunk: Lid may be chain, bolted or welded shut. Up to 8 places. 2 threaded rod can run through the frame. (up to 1" rod) no seam welding.
16. Any 5 lug rear end allowed. Can convert to leaf springs from any coil spring car.