

## **GENERAL RULES:**

1. **YOU GET ONE MINUTE TO MAKE AN AGGRESSIVE HIT, ONE MINUTE FOR RESTART, OR ONE MINUTE, IF YOU ARE HUNG UP. HITTING THE WALL OR A DISABLED CAR DOES NOT COUNT. NO SANDBAGGING OR HOLDING - YOU WILL BE DISQUALIFIED. THIS IS JUDGES DISCRETION AND JUDGES DECISIONS ARE FINAL!!!**
2. Drivers run at their own risk
3. Drivers must be 16 years or older, drivers under 18 must have notarized written consent of parent, if parent is not present at check in.
4. No one is allowed in pits under the age of 16 - must have picture ID for proof of age.
5. Only derby vehicles and one tow vehicle in pits - no spectator parking in pits.
6. Drivers must wear a seat belt or harness, helmet, and eye protection at all times when in the demo arena. Long sleeves, jeans, and/or fire suit are highly recommended.
7. No hot rodding in the pits, keep it at an idle.
8. DO NOT hit the driver's door - it sometimes happens, but if it looks intentional or careless, you will be disqualified
9. Two fires in one heat you are done.
10. All cars must enter the west gate of fairgrounds at least two hours before the event. If running late, call ahead. Pit gate opens at 2pm.
11. Judges reserve the right to disqualify any and/or all latecomers.
12. Drivers only must be present during inspection.
13. All drivers and crewmembers must attend the drivers meeting.
14. Judges reserve the right to re-inspect and disqualify any vehicle during the event.
15. Any harassment of judges or Fair Board members by drivers or pit person will result in disqualification and being banned from any further Fair Board Sponsored events.
16. Disqualification results in forfeiture of entry fee.
17. Any questions: give us a call, if it doesn't say you can do it, don't do it - Call 1<sup>st</sup>.

## **GENERAL PREPARATION RULES: \*\*These rules apply to all classes\*\***

1. All glass, plastic, and pot metal must be removed from the vehicle - nothing may remain in the bottom of the doors or trunks and all outside hardware must be removed - i.e. mirrors, lights, chrome, molding, screws, fiberglass, etc.
2. All cars must be standard make with no reinforcement or alterations to the frame unless specified.
3. All flammable materials inside the cab must be removed except necessary safety padding and seat.
4. All vehicles must have a driver's seat securely mounted to the floor.
5. Safety padding is recommended around the driver's area.
6. All vehicles must exhibit the ability to stop.
7. Vehicles must be safe to run and drive.
8. No dirty or vulgar language on vehicles.
9. Must have 12" x 12" (min) roof sign securely fastened with vehicle number visible or it will not run.
10. Vehicles may add protection over the driver's window.
11. Original gas tanks must be removed from the vehicle.

12. Your fuel lines must be inside the cab and may not go down through the floor and along the frame rail.
13. Electric fuel pumps are allowed.
14. Batteries must be securely mounted inside the cab and covered in a steel box.  
Steel transmission coolers will be allowed.  
ANY bolts, frame seats, battery boxes, fuel tanks, transmission coolers, etc. that extend through the frame or subframe will count as a body mount - please reference the class rules for how many are allowed.
15. 17. Floor shifters and headers are allowed.
  18. Trailer hitches must be removed.
    19. Any attempt to cover frames by buffing, grinding, coating with grease, glue, mud, etc. will result in immediate disqualification.
    20. Hoods must be open for inspection.
    21. A 12" x 12" (min) hole must be cut above the carburetor.
    22. NO split rims or studded tires.
16. Foam filled, doubled tires, and valve stem protectors are allowed.
17. Radiators must have a secured vented down and filled with water or ice only.
18. No snow, bar, or lug tires on drive wheels, regardless of tread condition.
19. If bumpers are removed, the bumper prods must be removed or trimmed (check class rules)
20. Bends or bubbles on the frame or subframe may be fixed on pre-ran vehicles - it may not extend more than 2" past affected area. The frame may be patched with 3 gauge (1/4") or thinner. Check specific class rules for more instructions for that class.